



# MOLYKOTE® 111 Compound provides food- and water-contact-approved O-ring lubrication and sealing in SWRO desalination

Lubricant application story: Joints

## MOLYKOTE® product

MOLYKOTE® 111 Compound

## Market segment

Desalination

## Component/application

Joints

## Major market

Maintenance, repair & overhaul (MRO)

## Customer's area of concern

### Customer's description of component

Desalination typically is accomplished through one of two processes: osmosis or reverse osmosis. The application detailed here was found in the process of seawater reverse osmosis (SWRO). SWRO is a filtration method that removes many types of large ions by applying pressure when it is on one side of a selective membrane. The process of applying an external pressure to reverse the natural flow of pure solvent is called reverse osmosis. During assembling of the membranes, a grease is needed to lubricate the O-ring that connects between the series of membranes and to seal the O-ring and the countersurface from high-pressure water (about 1,200 psi/82 Atm).

### Previous solution/product previously used

Lithium-based grease with EP additives

## Operational parameters (LETS)

### Load

1,200 psi (82 Atm)

### Environment

Seawater

### Temperature

Ambient

### Process description

Grease applied to O-rings using a swab

**MOLYKOTE®**



## Customer's critical requirements

### Problem details

The previously approved material did not have the appropriate certifications and approvals for food and water contact. The customer was looking for a product that was approved to FDA 21 CFR 175.300, NSF-51, NSF-61 and WRAS.

### Root-cause analysis

The previously used material was not certified appropriately for food and water contact.

## MOLYKOTE® *Smart Lubrication*™ solution selected

### Our product/differentiators

MOLYKOTE® 111 Compound *does* have a food approval and is certified by WRAS.

### Result: Our solution

MOLYKOTE® 111 Compound is a good, reliable product available in a variety of packaging sizes.

## Learn more: Contact us

To learn more about the advantages of using MOLYKOTE® 111 Compound for O-ring lubrication and sealing in SWRO desalination – or for other tough lubrication challenges – contact your MOLYKOTE® technical representative or visit [molykote.com](http://molykote.com).



DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.  
© 2011-2019 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

Form No. 85-3792A-01

(10/19) AGP16086

